

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 030 524 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:

23.08.2000 Bulletin 2000/34

(51) Int Cl.7: H04N 7/26

(21) Application number: 99440032.3

(22) Date of filing: 19.02.1999

(84) Designated Contracting States:

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE

Designated Extension States:

AL LT LV MK RO SI

(72) Inventor: Schuster Brigitte

67560 Rosheim (FR)

(74) Representative: Rausch, Gabriele, Dr. et al
Alcatel

Intellectual Property Department, Stuttgart

Postfach 30 09 29

70449 Stuttgart (DE)

(71) Applicant: ALCATEL

75008 Paris (FR)

(54) Method for encoding a digital image and coder

(57) The invention describes a method for coding residue data that are separated from a highly compressed base layer of data by taking a difference between the original and the reconstructed data signal using the residual signal with N bits in binary format and form N bit-planes within the bit planes are sorted a defined criteria.




Fig.4

EP 1 030 524 A1

Description

[0001] The present invention is related to the field of digital image processing and more particularly to a method for decoding and / or encoding digital images.

[0002] The storage of compressed streams of data and their transmission over heterogeneous and packed-based networks to end users connected with various physical links is greatly alleviated when the stream is scaleable temporary, spatially and qualitatively for video streams and qualitatively for voice or audio streams. Assuming these streams fulfill the later properties the problem consists in building hierarchical flows of packets such as each element of the whole transmission chain can first identify this hierarchy and secondly decide which flow of packets of which single packet can be neglected without compromising the global quality of the service. The quality of the service at each end user is in that case independent from the others. There is a strong link between the structure of the bit stream, the coding algorithm and the packetization process. The problem is building the optimal hierarchy for data packets.

[0003] The invention gives a solution with a method for coding residue data that are separated from a highly compressed base layer of data by taking a reference from the original and reconstructed coefficients of a mathematical transformation of data, using the residue signal with N bits in binary format and form N bit-planes, characterized in that the bit planes are sorted by a defined criteria. Every kind of mathematical transformation can be used as e.a. a discrete cosine transform, a discrete wavelet transform or fast Fourier transform.

[0004] An example is shown in the figures and described in the following description.

Fig. 1 shows the taking of residue between original and lower boundary point of quantization bin

Fig. 2 Scheme of coding

Fig. 3 Bit planes

Fig. 4 Application example

Fig. 5 Bit-plane coder.

[0005] Qualitative capable streams are usually structured into a base layer and at least one enhancement layer. This is for example known from the proposals for a MPEG-4 Standard published Dec. 1998 "Coding of moving pictures and associated audio" in the Internet. The related coding scheme produces a highly compressed base layer which is known in the proposal as visual IS layer. The residual information is used to produce either several enhancement layers or only one progressive enhancement layer. In this paper a method of "Fine Granularity Scalability" FGS for natural video signals is proposed which includes a description of the syntax and encoding/ decoding procedures for this layer. In this paper a coding scheme for bit plane encoding is proposed ordering the bit-planes in bit-plane from the most significant bit (MSB) to the bit-plane of the less significant bit (LSB).

cant bit (LSB).

[0006] The task of the invention is to use the same bandwidth to optimize the signal to noise ratio of the transmitted data and the quality of the signal. To solve this problem the bit-plane coding scheme is modified so that a statistic table is built up to give a different order of a bit-planes for getting better quality at the same bandwidth of transmission. The inventional proposal has the advantage that for the same bandwidth the quality of the information is enhanced. The method can easily be implemented as a function in the network independent from the coder itself. Following the MPEG 2 Standard which is related to the ISO/IEC 13818 Standard a special algorithm is defined which only fixes the syntax and the semantic of the bit stream and in particular the functional elements of the decoder. The basis of the coding is a hierarchy in form of six layers: sequence layer, group of pictures layer, picture layer, slice layer, macroblock layer and block layer. A MPEG 2 image is coded first by a block transformation and a quantization using a discrete cosine transformation scheme for the transformation. Afterwards a run length coding and a variable length coding simplifies the data to transmit. MPEG 2 uses no bit-plane sorting method. The bit-plane coding takes place after the quantization step but adding the computation of the residual data. On the encoder side the coding technique includes the following operations:

Taking a residue between the original DCT coefficient and a reference point determined by a quantized DCT coefficient.

Bit-plane encoding of the absolute value of the residual signal.

[0007] Selective encoding of the signs of the residue signal.

[0008] For taking the residue the reference mode method is taken. In the reference method the difference between the original and the lower boundary point of the quantization bin except the 0 bin as shown in Fig. 1 is taken. In the reference method the residue from the positive side remains positive and the residue from the negative side remains negative, taking the residue is equivalent to moving the origin to the reference point. Therefore the probability of the residue becomes the one shown in the lower half of Fig. 1 which preserves the shape of the original non uniform distribution. The bit-plane coding is started for the residual information which is divided from the basis data stream.

[0009] Fig. 2 shows a scheme of the data stream of a source data, e.a. a 8 x 8 matrix which is transformed by a discrete cosine transformation DCT then quantized in a quantizer 2 and coded by entropy encoder 3, e.g. run length coding RLC and a variable length coding VLC. The basis data layer is packetized in a packetizer. The residual information which is divided from the main stream after the discrete cosine transformation 2 is connected to a inverse quantizer 2a and then handled in a bit-plane coding scheme. The result is sent to the

packetizer, too.

The packetiser is not mandatory for the inventional coding scheme. After taking residues of all DCT- coefficient in a 8 x 8 block bit-plane is used to code the absolute values of the residue. The major conceptual difference between the bit coding method and run length coding method is that bit-plane coding method considers each absolute residue value as a binary number of several bits instead of a decimal integer of a certain value. The 64 absolute values of the residue signal are ordered into a one dimensional array. The bit-plane coding method can be described as a following procedure: Find the maximum value of all the absolute values of the residue signals in a VOP (Video Object Plane) and find the minimum number of bit N needed to represent this maximum value in the binary format. N is the number of bit-planes for this Video Object Plane and is coded in the VOP header of the enhancement layer. Within each 8 x 8 block represent every one of the 64 absolute values of the residue signal with N bits in the binary format and form N bit-planes. The bit-plane is defined as an array of 64 bits taking one from each absolute value of the residue of the same significant position. Starting from a bit-plane which have a highly statistical probability two dimensional symbols are formed of two components

- a) number of consecutive 0 before a 1 this is RUN
- b) whether there are any 1's left on this bit-plane e. g. end of plane EOP.

If a bit-plane after the most significant plane contains all zeros a special symbol or zero is formed to represent an all zero bit-plane. Two-dimensional VLC-tables are used to transform the planes to a code-word. In the bit-plane coding each bit-plane of the residual samples in a block are coded one after the other.

[0010] Bit-planes of a sample which is seen in Fig. 3 have the value 69. Bit 6 is the most significant bit and bit 0 is the less significant bit. Usually we say that the most significant bit is more important than the less significant bit. So usually the highest priority is given to the most significant bit MSB. Now we have to see the statistical probability to have a 1 in the bit 6 plane for the whole video image point. The statistical probability is very low to get a 1 for the whole image. An analysis of some video sequences shows that when the MSB plane is missing, the visual degradation is not as high as proposed. Medium bits are more important, e.g. bit plane 2 for our Fig. 3. So the sorting of the bit-planes can be done in a different way not starting with the most significant bit but with a bit-plane of high statistical value. One method to have a different sorting criteria is to compute the peak signal to noise ratio (PSNR) of the reconstructed signal with a missing bitplane. So we get a statistical table that is built by the PSNR versus the bit-plane. The PSNR allows to sort the data in a specific way. From the less important PSNR to the most important PSNR very close values of this criteria cannot change the sorting

scheme. It is possible to define a specific threshold for changes in the criteria to change the sorting scheme. After the sorting of the bit-planes each bit-plane is converted into symbols and coded using the VLC tables. Based on their locations in the bit-planes different VLC tables are used for coding the code-words. The further procedures are known from the publication of MPEG 4 "Coding of moving pictures and associated audio" Fig. 4 shows an encoder which is able to realize the inventional method. First a discrete cosine transformation 1 is made by a special transformation means. The transformation means 1 is connected to a quantizing means 2 and the quantizing means 2 is connected to an encoder 3. The output of the encoder 3 is connected to the packetizer 4. The residual information of the transformation 1 is fed into a inverse quantizer 2a and an inverse transformation 1a. The data stream of this transformation 1a is added to the original source stream, to get the residual data stream. The residual data stream is transformed in a transformation 1 b and fed into a bit-plane coder 5. The output of the bit-plane coder is connected directly or over an entropy decoder 3a to the packatizer 4.

[0011] In fig. 5 the bit-plane coder 5 includes means for bit-plane encoding of the absolute values of the residue signal 6 sorting means for sorting bit-planes 7 after a special sorting scheme, and means for detecting 8 a necessary change in the sorting scheme using fixed threshold values. The bit plane coder 5 can include an entropy decoder 3.

[0012] The coding method is working for video, audio and voicedata streams. For the sorting of the bitplanes other criteria then that describes in the preferred embodiment are possible. The criteria must be defined by the best system performance.

Claims

1. Method for coding residue data that are separated from a highly compressed base layer of data by taking a reference from the original and reconstructed coefficients of a mathematical transformation of data, using the residue signal with N bits in binary format and form N bit-planes, characterized in that the bit planes are sorted by a defined criteria.
2. Method for coding residue data that are separated from a highly compressed base layer of data by taking a reference from the original and reconstructed coefficients of a mathematical transformation of data, using the residue signal with N bits in binary format and form N bit-planes, characterized in that the bit planes are sorted by the peak signal to noise ratio of the reconstructed signal with a missing bit-plane..
3. Method for coding according to claim 2, character-

ized in that the sorting of the bit-planes can be influenced by a predefined figure.

4. Method for coding according to claim 3, characterized in that the predefined figure changes if the changes in the statistically product over come a predefined threshold. 5
5. Coder for coding a data stream including transformation means 1, quantizing means 2 and the quantizing means 2 are connected to a encoder 3 encoding the data stream with a run length encoding and a variable length encoding, and connected o an output ,with feeding residual information of the transformation 1 into a bit-plane coder 5 that is connected to the output. 10 15
6. Coder according to claim 5 including a bit plane coder 5 with means for bit-plane encoding of the absolute values of the residue signal 6, sorting means for sorting bit-planes 7 after a special sorting scheme, and means for detecting 8 a necessary change in the sorting scheme using fixed threshold values. 20 25

30

35

40

45

50

55

Fig.1





Fig.3

Bit6	Bit5	Bit4	Bit3	Bit2	Bit1	Bit0
1	0	0	0	1	0	1




Fig. 4




Fig. 5



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 99 44 0032

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION
X	US 5 768 535 A (NORTHCUTT J DUANE ET AL) 16 June 1998 (1998-06-16) * abstract * * column 7, line 16-27 * * column 8, line 1 - line 16 * * column 10, line 10 - line 29 * * column 12, line 33 - line 45 * * column 13, line 3 - column 14, line 58 *	1-4	H04N7/26
X	ORDENTLICH E, WEINBERGER M, SEROUSSI G : "A low-complexity modeling approach for embedded coding of wavelet" PROCEEDINGS DCC '98 DATA COMPRESSION CONFERENCE ,30 March 1998 (1998-03-30) - 1 April 1998 (1998-04-01), pages 408-417, XP002110371 Los Alamitos, CA, USA, IEEE Comput. Soc, USA * abstract * * page 412, line 26 - line 33 * * page 410, line 12 - line 33 *	1,2	
			TECHNICAL FIELDS SEARCHED
X	US 5 748 786 A (ALLEN JAMES D ET AL) 5 May 1998 (1998-05-05) * column 15, line 29 - line 54 *	1,2	H04N
A	WO 98 19273 A (BONE DONALD JAMES ;UNIV AUSTRALIAN (AU); COMMW SCIENT IND RES ORG) 7 May 1998 (1998-05-07) * abstract * * claims 1-9 * * page 8, line 9 - line 20 *	1,2	
A	WO 97 21302 A (DARTMOUTH COLLEGE ;DANSKIN JOHN M (US); DAVIS GEOFFREY (US)) 12 June 1997 (1997-06-12) * abstract; figure 2 *	1,2	
-/--			
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 27 July 1999	Examiner Giannotti, P
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03.92 (P46021)

European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 99 44 0032

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION
A	US 4 698 689 A (TZOU KOU-HU) 6 October 1987 (1987-10-06)	1,2	
X	* abstract *	5,6	
A	WALLACE G K: "THE JPEG STILL PICTURE COMPRESSION STANDARD" COMMUNICATIONS OF THE ASSOCIATION FOR COMPUTING MACHINERY, vol. 34, no. 4, 1 April 1991 (1991-04-01), pages 30-44, XP000228786 ISSN: 0001-0782	1,2	
X	* page 40, column C, line 8 - page 41, left-hand column, line 39; figure 10 *	5,6	
A	US 4 933 762 A (GUICHARD JACQUES ET AL) 12 June 1990 (1990-06-12) * abstract; figure 2 *	1,2,5,6	
A	US 5 155 592 A (VERBIEST WILLEM J A ET AL) 13 October 1992 (1992-10-13) * abstract; figure 1 *	1,2,5,6	TECHNICAL FIELDS SEARCHED
A	EP 0 618 727 A (SONY CORP) 5 October 1994 (1994-10-05) * abstract; figure 2 *	1,2,5,6	
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 27 July 1999	Examiner Giannotti, P
CATEGORY OF CITED DOCUMENTS		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons S : member of the same patent family, corresponding document	
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document			

EPO FORM 1508 03.82 (P04/01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 44 0032

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

27-07-1999

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5768535 A	16-06-1998	US 5621660 A	15-04-1997
		EP 0739140 A	23-10-1996
		JP 9163362 A	20-06-1997
US 5748786 A	05-05-1998	DE 19534943 A	28-03-1996
		FR 2724791 A	22-03-1996
		FR 2724792 A	22-03-1996
		GB 2293733 A, B	03-04-1996
		GB 2293734 A, B	03-04-1996
		GB 2302244 A, B	08-01-1997
		GB 2302245 A, B	08-01-1997
		GB 2302488 A, B	15-01-1997
		GB 2305829 A, B	16-04-1997
		JP 8139935 A	31-05-1996
		NL 1001248 C	04-06-1997
		NL 1001248 A	21-03-1996
		US 5867602 A	02-02-1999
		US 5881176 A	09-03-1999
WO 9819273 A	07-05-1998	AU 4693897 A	22-05-1998
WO 9721302 A	12-06-1997	AU 1329697 A	27-06-1997
US 4698689 A	06-10-1987	NONE	
US 4933762 A	12-06-1990	FR 2625060 A	23-06-1989
		DE 3874703 A	22-10-1992
		EP 0321318 A	21-06-1989
		JP 1264324 A	20-10-1989
		JP 2661220 B	08-10-1997
US 5155592 A	13-10-1992	WO 9105439 A	18-04-1991
		AU 635771 B	01-04-1993
		AU 6265590 A	11-04-1991
		DE 68916038 D	14-07-1994
		DE 68916038 T	27-10-1994
		EP 0446209 A	18-09-1991
		JP 2780864 B	30-07-1998
		JP 3179992 A	05-08-1991
EP 0618727 A	05-10-1994	JP 6133284 A	13-05-1994
		DE 69323996 D	22-04-1999
		WO 9409594 A	28-04-1994
		US 5850261 A	15-12-1998

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82